



PETROCHEMICAL PALLET (Export) [09] 09-EX





High quality plastic pallets with special dimensions (1400x1100x150 mm). 09-EX pallet having idea size containing mesh type surface and anti-slip rubbers for the safe and efficient handling of bulk bags and super sacks. It's especially designed for export shipments in the petrochemical industry.

TECHNICAL DATA

Pallet Name	Export Pallet
Dimensions LxWxH (mm)	1400 x 1100 x 150
CODE	09-EX
Static Loading (kg)	5000
Dynamic Loading (kg)	1500
Structure	
Runners	N/A
Standard Color	•
Container Load [40' HC]	270 PCs
Standard Truck Load	420 PCs
Rackable	✓

REQUEST OPTIONS

Customized Color

Client Logo Printed

Client LOGO Engraved

Anti-Slip Rubber

ADVANTAGES

- Anti-impact perimeter
- Large window operations for easy handling
- Plastic pallets have fewer or no repairs.
- Plastic pallets improve efficiencies due to standard dimensions and lack of broken board.
- Plastic pallets offer better product protection no nails or broken boards to damage payload.
- ✓ Plastic pallets offer better stability no damaged or missing boards causing spills or falling stacks.
- Plastic pallets improve safety and lower workers compensation claims.
- Plastic pallets allow for greater utilization of warehouse space stability and higher stacking.

Recommendations for use

- Do not stack more than 30 pallets, which is equivalent to a height of 4.65 m when empty.
- Once stacked in height check that they are properly fitted.
- The values indicated are approximate and are based on practical experience and ISO 86111-, evenly distributed load over pallet surface, at ambient temperature (23° C) for a specific time. Different load conditions produce different values that have to be checked at the customer's request. Any deterioration or breakage in the pallet may vary these results.
- Due to the characteristics of plastic materials and manufacturing process, the dimensions and the weight of the pallets may present certain tolerances.
- The specification can be affected in case of alteration of the product with parts and / or materials different from those approved by the RePall quality department.
- RePall reserves the right to modify any information herein indicated without prior notice.
- Any warranty, specification or liability on the part of RePall will be terminated in case of modification of the product with spare parts not supplied by RePall.









